

Pro Power Blue Antifreeze & Summer Coolant

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 Product identifier**

Product Name Pro Power Blue Antifreeze & Summer Coolant
Product code X675
Unique Formula Identifier (UFI) A1E0-T0M6-V00S-XP6M

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Antifreeze liquid. Antifreeze for vehicles.
Uses Advised Against Not known.

1.3 Details of the supplier of the safety data sheet**Manufacturer**

Company Identification Rapid Group UK
Address of Manufacturer Rutland Mill,
Adelaide Street,
Bolton,
Postal code BL3 3NY
Telephone: 01204 324 268

Supplier

Company Identification Rapid Ireland
Address of Supplier Rock Street,
Tralee,,
Co Kerry
Postal code V92 WR9P
Telephone: +353 151 363 47

1.4 Emergency telephone number

Emergency Phone No. 999
Contact NHS

SECTION 2: HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

Regulation (EC) No. 1272/2008 (CLP) Acute Tox. 4 :Harmful if swallowed.
STOT RE 2 :May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

According to Regulation (EC) No. 1272/2008 (CLP)
Product Name Pro Power Blue Antifreeze & Summer Coolant
Contains ethanediol ethylene glycol, sodium 2-ethylhexanoate

Pro Power Blue Antifreeze & Summer Coolant

Hazard Pictogram(s)



GHS08



GHS07

Signal Word(s)

Warning

Hazard Statement(s)

H302: Harmful if swallowed.

H373: May cause damage to organs through prolonged or repeated exposure.

Precautionary Statement(s)

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash hands and exposed skin thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P301+P312: IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

P501: Dispose of contents in accordance with local, state or national legislation.

Unique Formula Identifier (UFI)

A1E0-T0M6-V00S-XP6M

2.3 Other hazards

None known.

2.4 Additional Information

For full text of H/P Statements see section 16.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / REACH Registration No.	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
ethanediol ethylene glycol	107-21-1	203-473-3	45-100	Acute Tox. 4 H302 STOT RE 2 H373	GHS08 GHS07
sodium 2-ethylhexanoate	19766-89-3	243-283-8	<4	Repr. 2 H361d	GHS08

HAZARDOUS INGREDIENT(S)	CAS No.	Specific Concentration Limit	M-factor	ATE
ethanediol ethylene glycol	107-21-1			Acute Tox. 4 (H302) : 500.000

Pro Power Blue Antifreeze & Summer Coolant

Contains no non-classified vPvB substances or substances with a Union workplace exposure limit.

For full text of H/P Statements see section 16.

3.2 Mixtures

Not applicable.

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures**

Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Skin Contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye Contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.
Ingestion	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation:	Vapours in high concentrations are anaesthetic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Central nervous system depression.
Ingestion	Ingestion of large amounts may cause unconsciousness. Causes damage to organs (Kidneys) through prolonged or repeated exposure if swallowed
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	May cause temporary eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Notes for the doctor	If several ounces (60 - 100 ml) of ethylene glycol have been ingested, early administration of ethanol may counter the toxic effects (metabolic acidosis, renal damage). Consider hemodialysis or peritoneal dialysis & thiamine 100 mg plus pyridoxine 50 mg intravenously every 6 hours. If ethanol is used, a therapeutically effective blood concentration in the range of 100 - 150 mg/dl may be achieved by a rapid loading dose followed by a continuous intravenous infusion. Consult standard literature for details of treatment. 4-Methyl pyrazole (Antizol®) is an effective blocker of alcohol dehydrogenase and should be used in the treatment of ethylene glycol (EG), di- or triethylene glycol (DEG, TEG), ethylene glycol butyl ether (EGBE), or methanol intoxication if available. Fomepizole protocol: loading dose 15 mg/kg intravenously, follow by bolus dose of 10 mg/kg every 12 hours; after 48 hours, increase bolus dose to 15 mg/kg every 12 hours. Continue fomepizole until serum methanol, EG, DEG, TEG or EGBE are undetectable. The signs and symptoms of poisoning include anion gap metabolic acidosis, CNS depression, renal tubular injury, and possible late stage cranial nerve involvement. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. In severe
----------------------	--

Pro Power Blue Antifreeze & Summer Coolant

poisoning, respiratory support with mechanical ventilation and positive end expiratory pressure may be required. Maintain adequate ventilation and oxygenation of the patient. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. If burn is present, treat as any thermal burn, after decontamination. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media**

Suitable Extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2 Special hazards arising from the substance or mixture

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Ketones. Aldehydes.

5.3 Advice for firefighters

Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Contain and collect extinguishing water.
Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of spray mist and contact with skin and eyes. Provide adequate ventilation.

6.2 Environmental precautions

Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Absorb spillage with inert, damp, non-combustible material. Flush contaminated area with plenty of water. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4 Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling**

Avoid spilling. Avoid contact with skin and eyes. Avoid inhalation of vapours and spray/mists. Provide adequate ventilation.

7.2 Conditions for safe storage, including any incompatibilities

Pro Power Blue Antifreeze & Summer Coolant

Storage temperature Store in tightly-closed, original container in a dry, cool and well-ventilated place.
Storage life Stable under normal conditions.
Incompatible materials None known.

7.3 Specific end use(s)

Antifreeze liquid. Antifreeze for vehicles.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

Occupational Exposure Limits						
SUBSTANCE.	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
Ethane-1,2-diol Particulate	107-21-1		10			Sk
Ethane-1,2-diol vapour	107-21-1	20	52	40	104	Sk

Region Source
United Kingdom UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark Notes
Sk Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

8.2 Exposure controls

8.2.1. Appropriate engineering controls Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

8.2.2. Personal protection equipment



Eye Protection

The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard (EN166).



Skin protection

Use protective gloves. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Butyl rubber. Polyvinyl chloride (PVC). To protect hands from chemicals, gloves should comply with European Standard (EN374).



Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P3. EN 136/140/141/145/143/149



Thermal hazards

None known.

8.2.3. Environmental Exposure Controls Avoid release to the environment.

Pro Power Blue Antifreeze & Summer Coolant**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties**

Physical state	Liquid.
Colour	Blue.
Odour	Mild.
Melting point/freezing point	Not known.
Boiling point or initial boiling point and boiling range	Not known.
Flammability	Not known.
Lower and upper explosion limit	Not known.
Flash Point	Not known.
Auto-ignition temperature	Not known.
Decomposition Temperature	Not known.
pH	Not known.
Kinematic Viscosity	Not known.
Solubility	Solubility (Water) : Soluble in water. Solubility (Other) : Not known.
Partition coefficient n-octanol/water (log value)	Not known.
Vapour pressure	Not known.
Density and/or relative density	1.06 - 1.14.
Relative vapour density	Not known.
Particle characteristics	Not known.

9.2 Other information

None.

SECTION 10: STABILITY AND REACTIVITY**10.1 Reactivity**

None anticipated.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Will not polymerise.

10.4 Conditions to avoid

Avoid excessive heat for prolonged periods of time.

10.5 Incompatible materials

Strong oxidising agents. Strong acids. Strong alkalis.

10.6 Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Aldehydes. Ketones. Oxides of the following substances: Carbon.

SECTION 11: TOXICOLOGICAL INFORMATION

Pro Power Blue Antifreeze & Summer Coolant**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute toxicity - Ingestion	Harmful if swallowed.
Acute toxicity - Skin Contact	Not classified.
Acute toxicity - Inhalation	Not classified.
Skin corrosion/irritation	Not classified.
Serious eye damage/irritation	Not classified.
Skin sensitization data	Not classified.
Respiratory sensitization data	Not classified.
Germ cell mutagenicity	Not classified.
Carcinogenicity	Not classified.
Reproductive toxicity	Not classified.
Lactation	Not classified.
STOT - single exposure	Not classified.
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not classified.

11.2 Information on other hazards

Not known.

SECTION 12: ECOLOGICAL INFORMATION**12.1 Toxicity**

Toxicity - Aquatic invertebrates	Low toxicity to invertebrates.
Toxicity - Fish	Low toxicity to fish.
Toxicity - Algae	Low toxicity to algae.
Toxicity - Sediment Compartment	Not classified.
Toxicity - Terrestrial Compartment	Not classified.

12.2 Persistence and degradability

The product is expected to be biodegradable.

12.3 Bioaccumulative potential

The product is not bioaccumulating.

12.4 Mobility in soil

The product is soluble in water.

12.5 Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6 Endocrine disrupting properties

None known.

12.7 Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

Pro Power Blue Antifreeze & Summer Coolant**13.1 Waste treatment methods**

Waste should be treated as controlled waste. Do not puncture or incinerate, even when empty.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

Not classified as hazardous for transport.

14.1 UN number or ID number

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Not classified as a Marine Pollutant.

14.6 Special precautions for user

Not known

14.7 Maritime transport in bulk according to IMO instruments

Not known

SECTION 15: REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

European Regulations - Authorisations and/or Restrictions On Use

Candidate List of Substances of Very High Concern for Authorisation Not listed

REACH: ANNEX XIV list of substances subject to authorisation Not listed

REACH: Annex XVII Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles ethanediol ethylene glycol (107-21-1)

Community Rolling Action Plan (CoRAP) Not listed

Regulation (EU) N° 2019/1021 of the European Parliament and of the Council on persistent organic pollutants Not listed

Regulation (EC) N° 1005/2009 on substances that deplete the ozone layer Not listed

Regulation (EU) N° 649/2012 of the European Parliament and of the Council

Not listed

Not listed

Not listed

Not listed

Not listed

Not listed

Not listed

Not listed

Not listed

Pro Power Blue Antifreeze & Summer Coolant

concerning the export and import of
hazardous chemicals

National regulations

Other

Not known.

15.2 Chemical Safety Assessment

A REACH chemical safety assessment has not been carried out.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

LEGEND

Hazard Pictogram(s)



GHS08



GHS07

Hazard classification

Acute Tox. 4 : Acute toxicity, Category 4

Repr. 2 : Reproductive toxicity, Category 2

STOT RE 2 : Specific target organ toxicity — repeated exposure, Category 2

Hazard Statement(s)

H302: Harmful if swallowed.

H361d: Suspected of damaging the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

Precautionary Statement(s)

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash hands and exposed skin thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P301+P312: IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell.

P314: Get medical advice/attention if you feel unwell.

P330: Rinse mouth.

P501: Dispose of contents in accordance with local, state or national legislation.

Acronyms

ATE : Acute Toxicity Estimate

CAS : Chemical Abstracts Service

CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of
substances and mixtures

DNEL : Derived No Effect Level

EC : European Community

EINECS : European Inventory of Existing Commercial Chemical Substances

LTEL : Long term exposure limit

Pro Power Blue Antifreeze & Summer Coolant

PBT : Persistent, Bioaccumulative and Toxic

PNEC : Predicted No Effect Concentration

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

STEL : Short term exposure limit

STOT : Specific Target Organ Toxicity

vPvB : very Persistent and very Bioaccumulative

Key literature references and sources for Regulation (EC) No. 1272/2008 (CLP)
data used to compile the SDS

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Rapid Group UK gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Rapid Group UK accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.