

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 Product identifier**

Product Name Pro Power 5W/30 C2
Product code A326

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Lubricating oil
Uses Advised Against Not known.

1.3 Details of the supplier of the safety data sheet**Manufacturer**

Company Identification Rapid Group UK
Address of Manufacturer Rutland Mill,
Adelaide Street,
Bolton,
Postal code BL3 3NY
Telephone: 01204 324 268

Supplier

Company Identification Rapid Ireland
Address of Supplier Rock Street,
Tralee,
Co Kerry
Postal code V92 WR9P
Telephone: +353 151 363 47

1.4 Emergency telephone number

Emergency Phone No. 999
Contact NHS

SECTION 2: HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

Regulation (EC) No. 1272/2008 (CLP) Not classified as dangerous for supply/use.

2.2 Label elements

According to Regulation (EC) No. 1272/2008 (CLP)
Product Name Pro Power 5W/30 C2
Hazard Pictogram(s) None.
Signal Word(s) None.
Hazard Statement(s) None.
Precautionary Statement(s) P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.

Pro Power 5W/30 C2

2.3 Other hazards

EUH208: Contains: (Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts) May produce an allergic reaction.

2.4 Additional Information

None.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable.

3.2 Mixtures

| HAZARDOUS INGREDIENT(S) | CAS No. | EC No. / REACH Registration No. | %W/W | Hazard Statement(s) | Hazard Pictogram(s) |
|--|-------------|---------------------------------|---------|---|-------------------------|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified | 72623-87-1 | 276-738-4 | 50 - 90 | Asp. Tox. 1 H304 | GHS08 |
| reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate | 125643-61-0 | 406-040-9 | <0.5 | Aquatic Chronic 4 H413 | None |
| Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene | 68411-46-1 | 270-128-1 | < 1 | Aquatic Chronic 3 H412 | None |
| Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts | 85940-28-9 | 288-917-4 | < 2 | Skin Irrit. 2 H315 Eye Dam. 1 H318 Aquatic Chronic 2 H411 | GHS05 GHS07 GHS09 |
| Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts | 70024-69-0 | 274-263-7 | < 1 | Skin Sens. 1B H317 | GHS07 |
| reaction product of cocoalkyldiethanolamides and cocoalkylmonoglycerides and molybdenumtrioxide (1.75-2.2: 0.75-1.0:0.1-1.1) | | 430-380-7 | < 0.5 | Aquatic Chronic 2 H411 | GHS09 |
| calcium dihydroxide | 1305-62-0 | 215-137-3 | < 0.5 | Skin Irrit. 2 H315 Eye Dam. 1 H318 STOT SE 3 H335 | GHS05 GHS07 |
| diphenylamine | 122-39-4 | 204-539-4 | < 0.5 | Acute Tox. 3 H301 Acute Tox. 3 H311 Acute Tox. 3 H331 STOT RE 2 H373 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 | GHS06 GHS08 GHS09 |

Pro Power 5W/30 C2

| | | | | | |
|---|------------|-----------|-------|--|-------------------------|
| Distillates (petroleum), hydrotreated middle Gasoil - unspecified [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] | 64742-46-7 | 265-148-2 | < 0.5 | Asp. Tox. 1 H304 Skin Irrit. 2 H315 Acute Tox. 4 H332 Carc. 1B H350 STOT RE 2 H373 Aquatic Chronic 2 H411 | GHS08 GHS07 GHS09 |
|---|------------|-----------|-------|--|-------------------------|

| HAZARDOUS INGREDIENT(S) | CAS No. | Specific Concentration Limit | M-factor | ATE |
|---|------------|------------------------------|----------|---|
| diphenylamine | 122-39-4 | | | Acute Tox. 3 (H301) :100.000 Acute Tox. 3 (H311) :300.000 Acute Tox. 3 (H331) : 3.000 |
| Distillates (petroleum), hydrotreated middle Gasoil - unspecified [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C11 through C25 and boiling in the range of approximately 205 °C to 400 °C (401 °F to 752 °F).] | 64742-46-7 | | | Acute Tox. 4 (H332) : 11.000 |

Contains no non-classified vPvB substances.

Contains no non-classified substances with a Union workplace exposure limit.

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

| | |
|--------------|---|
| Inhalation | If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| Skin Contact | Wash skin with water. |
| Eye Contact | Flush eyes with water for at least 15 minutes. |
| Ingestion | Wash out mouth with water. |

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Pro Power 5W/30 C2

Unlikely to be required but if necessary treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media**

Suitable Extinguishing media Foam, CO₂ or dry Powder.

Unsuitable extinguishing media Do not use water.

5.2 Special hazards arising from the substance or mixture

None anticipated. Heating may cause decomposition.

5.3 Advice for firefighters

As appropriate for surrounding fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation. Wear suitable gloves if prolonged skin contact is likely.

6.2 Environmental precautions

Do not release large quantities into the surface water or into drains.

6.3 Methods and material for containment and cleaning up

Adsorb spillages onto sand, earth or any suitable adsorbent material.

6.4 Reference to other sections

See Also Section 8, 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling**

Not known.

7.2 Conditions for safe storage, including any incompatibilities

Storage temperature Ambient.

Storage life Stable under normal conditions.

Incompatible materials None known.

7.3 Specific end use(s)

Lubricating oil

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****8.1.1 Occupational Exposure Limits**

| Occupational Exposure Limits | | | | | | |
|------------------------------|-----------|------------------------|---------------------------------------|---------------|------------------------------|------|
| SUBSTANCE. | CAS No. | LTEL (8 hr TWA ppm) | LTEL (8 hr TWA mg/m ³) | STEL (ppm) | STEL (mg/m ³) | Note |
| Calcium hydroxide | 1305-62-0 | | 5 | | | |

Pro Power 5W/30 C2

| | | | | | | |
|---|-----------|--|----|--|----|--|
| Calcium hydroxide - Respirable fraction | 1305-62-0 | | 1 | | 4 | |
| Diphenylamine | 122-39-4 | | 10 | | 20 | |

Region: United Kingdom
Source: UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark: Notes

8.2 Exposure controls

8.2.1. Appropriate engineering controls Ensure adequate ventilation.

8.2.2. Personal protection equipment



Eye Protection Wear eye protection with side protection (EN166).



Skin protection Wear Impervious Gloves (EN374)



Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.



Thermal hazards None known.

8.2.3. Environmental Exposure Controls Do not release large quantities into the surface water or into drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state Liquid.
 Colour Amber
 Odour Characteristic odour
 Melting point/freezing point Not known.
 Boiling point or initial boiling point and boiling range Not known.
 Flammability Not known.
 Lower and upper explosion limit Not known.
 Flash Point >200 °C
 Auto-ignition temperature Not known.
 Decomposition Temperature Not known.
 pH Not known.
 Kinematic Viscosity =60 mm²/s 40 °C
 Solubility Solubility (Water) : Not known.
 Solubility (Other) : Not known.

Pro Power 5W/30 C2

| | |
|---|---|
| Partition coefficient n-octanol/water (log value) | Not known. |
| Vapour pressure | Not known. |
| Density and/or relative density | Density (g/ml) : 0.852 g/cm ³ - Relative density : 15 °C |
| Relative vapour density | Not known. |
| Particle characteristics | Not known. |

9.2 Other information**SECTION 10: STABILITY AND REACTIVITY****10.1 Reactivity**

None anticipated.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

None anticipated.

10.5 Incompatible materials

Not known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

| | |
|--------------------------------|--|
| Acute toxicity - Ingestion | Not classified. Calculated acute toxicity estimate (ATE) Calc ATE - 1000000.00000 |
| Acute toxicity - Skin Contact | Not classified. Calculated acute toxicity estimate (ATE) Calc ATE - 1000000.00000 |
| Acute toxicity - Inhalation | Not classified. Calculated acute toxicity estimate (ATE) Calc ATE - 30697.67000 |
| Skin corrosion/irritation | Not classified. |
| Serious eye damage/irritation | Not classified. |
| Skin sensitization data | Not classified. |
| Respiratory sensitization data | Not classified. |
| Germ cell mutagenicity | Not classified. |
| Carcinogenicity | Not classified. |
| Reproductive toxicity | Not classified. |
| Lactation | Not classified. |
| STOT - single exposure | Not classified. |
| STOT - repeated exposure | Not classified. |
| Aspiration hazard | Not classified. |

11.2 Information on other hazards

Not known.

SECTION 12: ECOLOGICAL INFORMATION**12.1 Toxicity**

| | |
|------------------------------------|--------------------------------|
| Toxicity - Aquatic invertebrates | Low toxicity to invertebrates. |
| Toxicity - Fish | Low toxicity to fish. |
| Toxicity - Algae | Low toxicity to algae. |
| Toxicity - Sediment Compartment | Not classified. |
| Toxicity - Terrestrial Compartment | Not classified. |

12.2 Persistence and degradability

Not known.

12.3 Bioaccumulative potential

Not known.

12.4 Mobility in soil

Not known.

12.5 Results of PBT and vPvB assessment

Not known.

12.6 Endocrine disrupting properties

None known.

12.7 Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods**

Dispose at suitable refuse site.

13.2 Additional Information

No special precautions are required for this product.

SECTION 14: TRANSPORT INFORMATION

Not classified as hazardous for transport.

14.1 UN number or ID number

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Pro Power 5W/30 C2

Not classified as a Marine Pollutant.

14.6 Special precautions for user

Not known

14.7 Maritime transport in bulk according to IMO instruments

Not known

SECTION 15: REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

European Regulations - Authorisations and/or Restrictions On Use

Candidate List of Substances of Very High Concern for Authorisation Not listed

High Concern for Authorisation

REACH: ANNEX XIV list of substances subject to authorisation Not listed

subject to authorisation

REACH: Annex XVII Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Carcinogens: category 1B (64742-46-7), Carcinogens: category 1B (72623-87-1), Carcinogens: category 1B (72623-87-1), Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts (85940-28-9), Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1), Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts (70024-69-0), reaction product of cocoalkyldiethanolamides and cocoalkylmonoglycerides and molybdenumtrioxide (1.75-2.2: 0.75-1.0:0.1-1.1) (), calcium dihydroxide (1305-62-0), diphenylamine (122-39-4)

Community Rolling Action Plan (CoRAP) Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene (68411-46-1)

Regulation (EC) N° 850/2004 of the European Parliament and of the Council on persistent organic pollutants Not listed

Regulation (EC) N° 1005/2009 on substances that deplete the ozone layer Not listed

Regulation (EU) N° 649/2012 of the European Parliament and of the Council concerning the export and import of hazardous chemicals Diphenylamine (122-39-4)

Regulation (EU) N° 649/2012 of the European Parliament and of the Council concerning the export and import of hazardous chemicals Diphenylamine (122-39-4)

Regulation (EU) N° 649/2012 of the European Parliament and of the Council concerning the export and import of hazardous chemicals Diphenylamine (122-39-4)

Regulation (EU) N° 649/2012 of the European Parliament and of the Council concerning the export and import of hazardous chemicals Diphenylamine (122-39-4)

Regulation (EU) N° 649/2012 of the European Parliament and of the Council concerning the export and import of hazardous chemicals Diphenylamine (122-39-4)

Regulation (EU) N° 649/2012 of the European Parliament and of the Council concerning the export and import of hazardous chemicals Diphenylamine (122-39-4)

National regulations

Other Not known.

15.2 Chemical Safety Assessment

A REACH chemical safety assessment has not been carried out.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

LEGEND

Hazard Pictogram(s) None.

Pro Power 5W/30 C2

GHS05: GHS: Corrosion

GHS06: GHS: Skull and crossbones

GHS07: GHS: Exclamation mark

GHS08: GHS: Health hazard

GHS09: GHS: Environment

Hazard classification

Acute Tox. 3 : Acute toxicity, Category 3

Asp. Tox. 1 : Aspiration hazard, Category 1

Acute Tox. 3 : Acute toxicity, Category 3

Skin Irrit. 2 : Skin corrosion/irritation, Category 2

Skin Sens. 1B : Skin sensitization, Category 1B

Eye Dam. 1 : Serious eye damage/irritation, Category 1

Acute Tox. 3 : Acute toxicity, Category 3

Acute Tox. 4 : Acute toxicity, Category 4

STOT SE 3 : Specific target organ toxicity — single exposure, Category 3

Carc. 1B : Carcinogenicity, Category 1B

STOT RE 2 : Specific target organ toxicity — repeated exposure, Category 2

Aquatic Acute 1 : Hazardous to the aquatic environment, Acute, Category 1

Aquatic Chronic 1 : Hazardous to the aquatic environment, Chronic, Category 1

Aquatic Chronic 2 : Hazardous to the aquatic environment, Chronic, Category 2

Aquatic Chronic 3 : Hazardous to the aquatic environment, Chronic, Category 3

Hazard Statement(s)

H301: Toxic if swallowed.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H350: May cause cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Pro Power 5W/30 C2

Precautionary Statement(s)

None.

Acronyms

ATE : Acute Toxicity Estimate

CAS : Chemical Abstracts Service

CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

DNEL : Derived No Effect Level

EC : European Community

EINECS : European Inventory of Existing Commercial Chemical Substances

LTEL : Long term exposure limit

PBT : Persistent, Bioaccumulative and Toxic

PNEC : Predicted No Effect Concentration

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

STEL : Short term exposure limit

STOT : Specific Target Organ Toxicity

vPvB : very Persistent and very Bioaccumulative

Key literature references and sources for Regulation (EC) No. 1272/2008 (CLP) data used to compile the SDS

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Rapid Group UK gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Rapid Group UK accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.