

TECHNICAL DATA SHEET

Pro Power

15W-40

1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Pro Power Ultra 15W-40 is a high quality mineral oil designed for use in turbo and non-turbo charged vehicles with petrol and diesel engines.

Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: A3/B3, A3/B4 & E2

API: CF & SL/CH-4

Mack: EO-L MAN: 271

PERTS IN HIGH QUALITY OIL

MB: 228.1 & 229.1

Volvo: VDS VW: 505.00 MTU: Type 1

Product Benefits

- * Manufactured from high quality mineral oils and high performance additives
- * Provides excellent level of engine cleanliness
- * Premium additives control the formation of lacquers and sludge



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A100-001	5020618210009
5 Litre	A100-005	5020618210016
20 Litre	A100-020	5020618210023
199 Litre	A100-199	5020618210030

Product Usage

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Revision: 1 | Date: 16/10/2024



TECHNICAL DATA SHEET

Pro Power

15W-40

1 Litre, 5 Litre, 20 Litre & 199 Litre

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	12.5	<16.3	14.05
Viscosity, CCS	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		10.62
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
NOACK Volatility	ASTM D5800	%		13	
Pour Point	ASTM D97	°c		-25	
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			104.34
Density	ASTM D792	@ 15°c			0.889

Safety Precautions

EXPERTS IN HIGH QUALITY OIL

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024