

TECHNICAL DATA SHEET

Pro Power 5W-30 GM 1 Litre & 5 Litre

Product Description

PERTS IN HIGH QUALITY OIL

Pro Power Ultra 5W/30 GM is formulated primarily to meet GM longlife requirements using the most advanced additive technology to produce a fuel efficient engine oil that has excellent high and low temperature performance and exceptional long term anti wear characteristics. Suitable for use in petrol & diesel engines where specified including: Vauxhall, Opel, Mercedes, BMW and Saab

Recommended for use by Pro Power for the

following manufacturer's specifications ACEA: A3/B4

ACEA: A3/B4 API: CF & SM/SL BMW: LL-01 & LL-98 GM: LL-A-025 & LL-B-025 MB: 229.5 VW: 505.00 & 502.00

- 1	MANICANO		-
- 1	PROM		10
- 1	5W-30		
	FULLY SYNTHETI HOTOR OIL FOR MULTI-VENICLE SERVIC	C REG CHECK	5W-30 GM
	HECONAUTORIO FOR USE N ACEA AUTO ACEA AUTO VIO GROUP VIOLOGIALISO VIO GROUP VIOLOGIALISO	Recodes Bare 2025 Vauxanti Ger 11-4-025 Berley LL-01-LL-00	HOTOR OLL Patrix autore wall a transmission A diff a high product of the second and A diff a high product of the sec
	,	-005	A474-001
		PROHPOM	

* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A474-001	5020618210887
5 Litre	A474-005	5020618210894

Product Benefits

- * Latest synthetic technology motor oil
- * Formulated to give excellent fuel efficiency
- * Rapid circulation from cold start up

Product Usage

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com



Pro Power 5W-30 GM 1 Litre & 5 Litre

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	9.3	<12.5	
Viscosity, CCS	ASTM D4684	mPa.s		<6600	
Total Base Number	ASTM D2896	mg KOH/g	10		
HTHS Viscosity	ASTM D4683	mPa.s	>3.5		
NOACK Volatility	ASTM D5800	%		10	
Pour Point	ASTM D97	°C		-27	

Safety Precautions

EXPERTS IN HIGH QUALITY OIL

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com