

# Pro Power 10W-40 SS

1 Litre, 5 Litre, 20 Litre & 199 Litre

### **Product Description**

Pro Power Ultra 10W-40 SS is a semi synthetic oil designed for use in turbo and non-turbocharged vehicles with petrol and diesel engines

Recommended for use by Pro Power for the following manufacturer's specifications ACEA: A3/B3 & A3/B4 API: SL/CF MB: 229.1 VW: 505.00 & 502.00

### **Product Benefits**

**XPERTS IN HIGH QUALITY OIL** 

- \* Manufactured from high quality base oils and high performance additives
- \* Provides excellent level of engine cleanliness
- \* Premium additives control the formation of lacquers and sludge

		1				
	$\leq$			P		
<u>O</u> E	ROF	201				
1	OW-	<b>tr</b> 40 s				RA
H	EMI SYNTHET		P REG CHECK		OW-4C	SS P
	A21	15-005			NERA ASI'NA ASI'NA Mi Guid Mi Guid Manadana Yang Selataonan Manadana Basa (1931	5-001
C		PRO	POWER		A21	

MAINTAINS OEM WARRANTY\*

\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A215-001	5020618210047
5 Litre	A215-005	5020618210054
20 Litre	A215-020	5020618210061
199 Litre	A215-199	5020618210078

### **Product Usage**

Use as per the engine manufacturers recommendations,

# **Storage Instructions**

Store upright & sealed in a cool dry place & out of the reach of children.

# Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil



# **TECHNICAL DATA SHEET**

Pro Power 10W-40 SS

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	12.5	<16.3	13.46
Viscosity, CCS	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		11.25
Pour Point	ASTM D97	°c		-35	-33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		12	
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			81.77
Density	ASTM D792	@ 15°c			0.872
Viscosity Index	ASTM D2270				160.96

## **Safety Precautions**

EXPERTS IN HIGH QUALITY OIL

Please see our latest EC Safety Data Sheets for details.

### **Transport Classification**

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com