

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

**Pro Power**  
**5W-30 C3 VW**  
1 Litre, 5 Litre, 20 Litre & 199 Litre

### Product Description

Pro Power Ultra 5W-30 C3 VW is a fully synthetic, low SAPS, fuel efficient motor oil suitable for use in both petrol and diesel engines. It is designed to give maximum protection to diesel particulate filters (DPF). Recommended for many modern vehicles, including those from Audi, VW, Skoda, Seat, BMW, Mercedes-Benz, Porsche and others.

### Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: C3  
API: SN  
BMW: LL-04  
MB: 229.51  
Porsche: C30  
VW: 504.00 & 507.00

### Product Benefits

- \* Suitable for long life service intervals
- \* Latest synthetic technology motor oil
- \* Formulated to give excellent fuel efficiency
- \* Protects sensitive exhaust after-treatment devices, such as DPF's - diesel particulate filters

### Product Usage

Use as per engine manufacturers recommendations.

### Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A331-001	5020618210313
5 Litre	A331-005	5020618210320
20 Litre	A331-020	5020618210337
199 Litre	A331-199	5020618210344

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*

Revision: 2 | Date: 20/01/2025

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

Pro Power

**5W-30 C3 VW**

1 Litre, 5 Litre, 20 Litre & 199 Litre

### Shelf Life

5 Years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	12.3
Total Base Number	ASTM D2896	mg KOH/g	7		8.33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
Viscosity, CCS	ASTM D4684	mPa.s		6600	
Pour Point	ASTM D97	°C		-36	
NOACK Volatility	ASTM D5800	%		<10	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			76.3
Density	ASTM D792	@ 15°C			0.85

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 2 | Date: 20/01/2025

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*