

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

### Pro Power 5W-30 RN17 1 Litre, 5 Litre & 20 Litre

#### Product Description

Pro Power Ultra 5W-30 RN17 is a fully synthetic low SAPS, fuel efficient motor oil suitable for use in both petrol and diesel engines, designed to give maximum protection to petrol & diesel particulate filters. Recommended for many modern vehicles, including those from Renault and others.

#### Recommended for use by Pro Power for the following manufacturer's specifications

MB: 226.52

ACEA: C3

Renault: RN17

#### Product Benefits

- \* Latest synthetic technology motor oil
- \* Formulated to give excellent fuel efficiency
- \* Prolong the life of after-treatment systems including catalytic converters and both diesel and petrol particulate filters

#### Product Usage

Use as per engine manufacturers recommendations.

#### Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

#### Shelf Life

5 Years from date of manufacture.

|                         |   |                    |
|-------------------------|---|--------------------|
| Appearance              | : | Amber liquid       |
| Odour                   | : | Characteristic     |
| Solubility              | : | Insoluble in water |
| Percentage of Biodiesel | : | Nil                |



\* Image for illustrative purposes only.

| Size     | Part No  | Barcode       |
|----------|----------|---------------|
| 1 Litre  | A335-001 | 5020618210443 |
| 5 Litre  | A335-005 | 5020618210450 |
| 20 Litre | A335-020 | 5020618210467 |

MAINTAINS OEM WARRANTY\*

Revision: 1 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

Pro Power

**5W-30 RN17**

1 Litre, 5 Litre & 20 Litre

| Test                       | Method     | Unit               | Min. | Max.  | Typical |
|----------------------------|------------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445  | mm <sup>2</sup> /s | 9.3  | <12.5 | 11.4    |
| Viscosity, Kinematic 40°C  | ASTM D445  | mm <sup>2</sup> /s |      |       | 66      |
| Density                    | ASTM D792  | @ 15°C             |      |       | 0.85    |
| Viscosity, CCS             | ASTM D4684 | mPa.s              |      | 6600  |         |
| Total Base Number          | ASTM D2896 | mg KOH/g           | 7.5  |       | 9.3     |
| HTHS Viscosity             | ASTM D4683 | mPa.s              | >3.5 |       |         |
| NOACK Volatility           | ASTM D5800 | %                  |      | <11   |         |

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*

Revision: 1 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)