

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

### Pro Power

## 0W-20 ECO-FE

1 Litre, 5 Litre, 20 Litre & 199 Litre

### Product Description

Pro Power Ultra 0W-20 ECO-FE is a fully synthetic low SAPS, fuel efficient motor oil suitable for use in both petrol and diesel engines, designed to give maximum protection to petrol and diesel particulate filters. The advanced formulation offers Low Speed Pre-Ignition (LSPI) protection. Recommended for many modern Vauxhall/Opel, BMW, Mercedes-Benz, Jaguar Land Rover, Hyundai, Kia, Toyota and others.

### Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: C5 & C6  
API: SN Plus, SN-RC & SP  
BMW: LL-14 FE+ & LL-17 FE+  
Chrysler: MS 12145  
Fiat: 9.55535-DSX & 9.55535-GSX  
Ford: WSS-M2C947-B1, WSS-M2C952-A1 & WSS-M2C962-A1  
MB: 229.71 & 229.72  
Opel: OV0401547  
STJLR: .03.5006 & .51.5122  
Volvo: VCC RBS0-2AE  
ILSAC: GF-6A



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A370-001	5020618210597
5 Litre	A370-005	5020618210603
20 Litre	A370-020	5020618210610
199 Litre	A370-199	5020618210627

### Product Benefits

- \* Advanced Fully Synthetic formulation
- \* Ideal choice in hot running engines where its prevention of deposits keeps turbochargers in optimum condition
- \* Protect after-treatment systems including petrol & diesel particulate filters

### Product Usage

Use as per engine manufacturers recommendations.

### Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Revision: 1 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*

# PRO+POWER ULTRA

## TECHNICAL DATA SHEET

Pro Power

**0W-20 ECO-FE**

1 Litre, 5 Litre, 20 Litre & 199 Litre

### Shelf Life

5 Years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm <sup>2</sup> /s	7.8	<9.3	8.52
Viscosity, CCS	ASTM D4684	mPa.s		<6200	5812
Total Base Number	ASTM D2896	mg KOH/g	8		
Pour Point	ASTM D97	°C		-48	
HTHS Viscosity	ASTM D4683	mPa.s	2.8	<2.9	
NOACK Volatility	ASTM D5800	%		11	
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s			45.452
Density	ASTM D792	@ 15°C			0.845

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024

For further information visit [www.propoweroil.com](http://www.propoweroil.com)

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY\*