

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power 5W-20 ECO FD 1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Pro Power Ultra 5W-20 ECO FD is a fully synthetic engine oil formulated for the latest intelligent Eco engines including those with stop/start technology. The carefully selected base stocks and synthetic additives give this multi-grade engine oil high levels of engine component protection as well as being fuel efficient.

Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: C5
API: SN/CF
Chrysler: MS 6395
Ford: WSS-M2C925-B & WSS-M2C948-B
ILSAC: GF-5
STJLR: .03.5004

Product Benefits

- * Premium motor oil recommended for many modern vehicles, including Ford EcoBoost petrol engines
- * Latest synthetic technology motor oil
- * Formulated to give excellent fuel efficiency
- * Rapid circulation on cold start up

Product Usage

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance : Amber liquid
Odour : Characteristic



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A471-001	5020618210764
5 Litre	A471-005	5020618210771
20 Litre	A471-020	5020618210788
199 Litre	A471-199	5020618210795

MAINTAINS OEM WARRANTY*

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power

5W-20 ECO FD

1 Litre, 5 Litre, 20 Litre & 199 Litre

Solubility : Insoluble in water
Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	6.9	<9.3	7.8
Viscosity, CCS	ASTM D4684	mPa.s		6600	4567
Total Base Number	ASTM D2896	mg KOH/g	8		9.795
HTHS Viscosity	ASTM D4683	mPa.s	2.6	<2.9	
NOACK Volatility	ASTM D5800	%		13	11
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			43.523
Viscosity Index	ASTM D2270				150.55
Density	ASTM D792	@ 15°C			0.849
Pour Point	ASTM D97	°C		-35	-39

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com