

TECHNICAL DATA SHEET

Pro Power 0W-30 LL

1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Pro Power Ultra 0W-30 LL is a fully synthetic formulated to meet the performance demands of modern petrol and diesel engines. Pro Power Ultra 0W/30 LL is a blend of the very latest in base oil and additive technology, designed for extended drain performance, especially suited for modern engines.

Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: A5/B5 API: SL/CF BMW: LL-01 FE Volvo: VCC 95200377 VW: 503.00

PERTS IN HIGH QUALITY OIL

ШX

Product Benefits

- * Latest synthetic technology motor oil
- * Formulated to give excellent fuel efficiency
- * Rapid circulation from cold

Product Usage

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance	:	Amber liquid		
Odour	:	Characteristic		
Solubility	:	Insoluble in water		
Percentage of Biodiesel	:	Nil		



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	A472-001	5020618210801
5 Litre	A472-005	5020618210818
20 Litre	A472-020	5020618210825
199 Litre	A472-199	5020618210832

For further information visit www.propoweroil.com

Revision: 1 | Date: 16/10/2024



TECHNICAL DATA SHEET

Pro Power 0W-30 LL

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	9.3	<12.5	9.99
Total Base Number	ASTM D2896	mg KOH/g	8		10.62
HTHS Viscosity	ASTM D4683	mPa.s	2.9	<3.5	
NOACK Volatility	ASTM D5800	%		13	
Viscosity, CCS	ASTM D4684	mPa.s		6200	
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			53.87
Density	ASTM D792	@ 15°c			0.845
Pour Point	ASTM D97	°c		-40	

Safety Precautions

EXPERTS IN HIGH QUALITY OIL

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com