

## TECHNICAL DATA SHEET

#### **Pro Power**

## 75W-80 MTF

1 Litre & 5 Litre

#### **Product Description**

Pro Power Ultra 75W-80 MTF is a premium fully synthetic, fuel efficient manual gearbox oil recommended for a variety of highly stressed manual gearboxes found in many cars and vans.

### Recommended for use by Pro Power for the following manufacturer's specifications

API: GL-4 & GL-5

PERTS IN HIGH QUALITY OIL

BMW: MTF LT-2, MTF LT-3 & MTF LT-4

Fiat: 9.55550-MZ1 & 9.55550-MZ6

Ford: WSD-M2C200-C & WSS-M2C200-D2

GM: 1940182, 1940764, 1940768, 1940004 & 19529104 Honda: Special MTF, Special MTF-II & Special MTF III

PSA: B71 2330

Volvo: 97308 & 97309

VW: G 052 178, G 052 512, G 052 726, G 060 726, G 009 317, G 052 171, G 052 527-A2, G 50 & G 70 726 A2

Nissan: MT-XZ & MT-XZ (JR Type)



\* Image for illustrative purposes only.

| Size    | Part No  | Barcode       |
|---------|----------|---------------|
| 1 Litre | B320-001 | 5020618211143 |
| 5 Litre | B320-005 | 5020618211150 |

### **Product Benefits**

- \* Latest technology additives ensure positive and problem free gear selection
- \* Excellent cold start fluidity ensuring fast circulation
- \* Exceptionally good high temperature stability ensuring maximum protection

#### **Product Usage**

Use as per vehicle manufacturers recommendations.

#### **Storage Instructions**

Store sealed and upright in a cool dry place & out of the reach of children.

Revision: 1 | Date: 16/10/2024



# **TECHNICAL DATA SHEET**

## **Pro Power**

## 75W-80 MTF

1 Litre & 5 Litre

#### **Shelf Life**

**EXPERTS IN HIGH QUALITY OIL** 

5 Years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

| Test                       | Method    | Unit   | Min. | Max. | Typical |
|----------------------------|-----------|--------|------|------|---------|
| Viscosity, Kinematic 100°c | ASTM D445 | mm²/s  | 7    | <11  | 10.01   |
| Viscosity, Kinematic 40°c  | ASTM D445 | mm²/s  |      |      | 56.91   |
| Density                    | ASTM D792 | @ 15°c |      |      | 0.85    |

#### **Safety Precautions**

Please see our latest EC Safety Data Sheets for details.

#### **Transport Classification**

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024