

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power

Auto D II

1 Litre, 5 Litre & 20 Litre

Product Description

Pro Power Ultra Auto D II is a mineral auto transmission fluid (ATF) for use in many modern automatic transmissions. Manufactured using highly refined oils and high performance additives.

Recommended for use by Pro Power for the following manufacturer's specifications

Allison: C4

CAT: TO-2

Ford: Mercon[®]174, WSS-M2C166-H & WSS-M2C138-CJ

MB: 236.7 & 236.1

ZF: TE-ML-09, TE-ML-11 & TE-ML-14

GM: Dexron II-D

Product Benefits

- * Compatible with materials found in automatic transmissions systems, such as seals and specialised plastic parts
- * Provides a quiet and smooth gear shift, with excellent frictional stability, anti-shudder & anti wear properties
- * Outstanding low temperature fluidity

Product Usage

Use as per vehicle manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance	:	Red liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	C300-001	5020618211174
5 Litre	C300-005	5020618211181
20 Litre	C300-020	5020618211198

Revision: 2 | Date: 20/01/2025

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power

Auto D II

1 Litre, 5 Litre & 20 Litre

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s			8.07
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			43.59
Density	ASTM D792	@ 15°C			0.864

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 2 | Date: 20/01/2025

For further information visit www.propoweroil.com