

# **TECHNICAL DATA SHEET**

Pro Power Auto D III 1 Litre, 5 Litre & 20 Litre

## **Product Description**

PERTS IN HIGH QUALITY OIL

Pro Power Ultra Auto D III is a premium semi synthetic auto transmission fluid (ATF) for use in many modern automatic transmissions. Compatible with materials found in automatic transmissions systems, such as seals and specialised plastic parts.

Recommended for use by Pro Power for the following manufacturer's specifications Allison: C4 & TES-389 Ford: Mercon® MB: 236.10, 236.5, 236.6, 236.7, 236.9, 236.1 & 236.8 Volvo: 97341 & 97340 CAT: TO-2 ZF: TE-ML-03D, TE-ML-04D, TE-ML-09, TE-ML-14B, TE-ML-16L, TE-ML-17C, TE-ML-02F, TE-ML-11A, TE-ML-11B & TE-ML-14A GM: Dexron III H MAN: 339 V1, 339 V2, 339 Z1, 339 Z2 & 339F Voith: 55.6335 (G607)

ULTRA AUTO DIII SEMI SYNTHETIC	
A CONTRACT OF THE OWNER OF THE OWNER OF THE OWNER OF THE OWNER	A CONTRACTOR OF

\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	C315-001	5020618211204
5 Litre	C315-005	5020618211211
20 Litre	C315-020	5020618211228

#### **Product Benefits**

- \* Provides a quiet and smooth gear shift, with excellent frictional stability, anti-shudder & anti wear properties
- \* Outstanding low temperature fluidity
- \* Can be used where a Dexron II product is specified

#### **Product Usage**

Use as per vehicle manufacturers recommendations.

#### Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Revision: 2 | Date: 20/01/2025



Pro Power Auto D III 1 Litre, 5 Litre & 20 Litre

EXPERTS IN HIGH QUALITY OIL

Shelf Life

5 Years from date of manufacture.

:	Red liquid
:	Characteristic
:	Insoluble in water
:	Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s			7.55
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			37.26
Density	ASTM D792	@ 15°c			0.848

## **Safety Precautions**

Please see our latest EC Safety Data Sheets for details.

## **Transport Classification**

Please see our latest EC Safety Data Sheets for details.

**MAINTAINS OEM WARRANTY\*** 

For further information visit www.propoweroil.com