

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power Auto MV

1 Litre, 5 Litre & 20 Litre

Product Description

Pro Power Ultra Auto MV is a next generation fully synthetic auto transmission fluid (ATF) designed for anti-shudder performance in modern transmissions. Compatible with materials found in automatic transmissions systems, such as seals and specialised plastic parts

Recommended for use by Pro Power for the following manufacturer's specifications

Allison: C4 & TES-295

Ford: Mercon[®]174, Mercon[®]174 V, WSS-M2C166-H, WSS-M2C195-A, WSS-M2C202-B & WSS-M2C924-C

GM: Dexron III H & 93160393

JASO: 1-A

MAN: 339 V1, 339 Z1 & 339 Z2

MB: 236.3, 236.5, 236.6, 236.7 & 236.9

Voith: 55.6335 (G607)

Volvo: 97340, 97341 & 11 61 540-8

ZF: TE-ML-03D, TE-ML-04D, TE-ML-14A, TE-ML-14B, TE-ML-16L & TE-ML-17C

ATF: SPII, SPIII & Type A, Suffix A (TASA)

Esso: LT71141ATF

Idemitsu: K17

JWS: 3309

Mopar: ATF+3 & ATF+4

Nissan: Matic J & Matic K

Saab: 3309 & 93 165 147

Texaco: ETL-8072B & N402

Toyota: T-IV

VW: G 052 990-A2 & G 055 025-A2



* Image for illustrative purposes only.

| Size | Part No | Barcode |
|----------|----------|---------------|
| 1 Litre | C325-001 | 5020618211259 |
| 5 Litre | C325-005 | 5020618211266 |
| 20 Litre | C325-020 | 5020618211273 |

Product Benefits

- * Provides a quiet and smooth gear shift, with excellent frictional stability, anti-shudder & anti wear properties
- * Outstanding low temperature fluidity
- * Exceeds the requirements of over 75 Asian, European and American motor manufacturers

Revision: 2 | Date: 20/01/2025

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power

Auto MV

1 Litre, 5 Litre & 20 Litre

Product Usage

Use as per vehicle manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

| | | |
|-------------------------|---|--------------------|
| Appearance | : | Red liquid |
| Odour | : | Characteristic |
| Solubility | : | Insoluble in water |
| Percentage of Biodiesel | : | Nil |

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|-----------|--------------------|------|------|---------|
| Viscosity, Kinematic 40°C | ASTM D445 | mm ² /s | | | 38.35 |
| Density | ASTM D792 | @ 15°C | | | 0.848 |
| Viscosity, Kinematic 100°C | ASTM D445 | mm ² /s | | | 7.291 |

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 2 | Date: 20/01/2025

For further information visit www.propoweroil.com

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*