

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power MV CHF 1 Litre

Product Description

Pro Power Ultra MV CHF is a fully synthetic fluid for use in hydraulic applications including power steering units, shock absorbers, hydro-pneumatic suspensions and traction control systems.

IMPORTANT: Do not mix with ATF or other Power Steering Fluids.

Recommended for use by Pro Power for the following manufacturer's specifications

Bentley: RH500
BMW/Mini: 82 11 0 148 132, 82 11 1 468 041 & 83 29 0 429 576
DIN: 51524 Part 3 (HVLP)
Ford: WSS-M2C204-A
ISO: 7308
MB: 345.00
Porsche: 000.043.203.33
Volvo: 11 61 529
VW: G 002 000-A2 & VW TL 52146.00
FENDT: X902 011 622
Mercedes-Benz: 001 989 24 0310, 001 989 24 0312 & Q1 32 0001
SAAB: 3032 380
ZF: TE-ML-02K
MAN: M3289



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	E100-001	5020618211389

Product Benefits

- * Can be used in convertible roof mechanisms
- * Premium synthetic fluid
- * Dyed green in colour for easy identification

Product Usage

Use as per vehicle manufacturers recommendations.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com

PRO+POWER ULTRA

TECHNICAL DATA SHEET

Pro Power
MV CHF
1 Litre

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

Appearance : Pale Green Liquid

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity Index	ASTM D2270		270		310

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

EXPERTS IN HIGH QUALITY OIL

MAINTAINS OEM WARRANTY*

Revision: 1 | Date: 16/10/2024

For further information visit www.propoweroil.com