

### **TECHNICAL DATA SHEET**

#### **Pro Power**

**ISO 46** 

20 Litre

#### **Product Description**

Pro Power Ultra ISO 46 is a premium grade mineral based hydraulic oil with excellent anti-wear properties to give maximum protection in the most demanding of systems whilst controlling rust, corrosion and oxidation.

# Recommended for use by Pro Power for the following manufacturer's specifications

US Steel: 127 Denison: HF-2 ISO: 6743-4

PERTS IN HIGH QUALITY OIL

Afnor: NFE E 48-600

Denison Filterability: TP02100 DIN: 51524 Part 2 (HLP)

SEB: 181.222

Sperry Vickers: I-286-S & M-2950-S

Thyssen: TH N-256132

VDMA: 24318



\* Image for illustrative purposes only.

Size	Part No	Barcode
20 Litre	E226-020	5020618211433

#### **Product Benefits**

- \* Anti-foam additive to control foam and assist with the quick release of air
- \* Suitable for a wide range of hydraulic systems and applications
- \* Not suitable for systems in which silver-plated components are used

#### **Product Usage**

Use as per the component manufacturers recommendations.

#### **Storage Instructions**

Store sealed and upright in a cool dry place & out of the reach of children.

#### **Shelf Life**

5 Years from date of manufacture.

Appearance : Amber liquid

Odour : Characteristic

Revision: 1 | Date: 16/10/2024



## **TECHNICAL DATA SHEET**

#### **Pro Power**

**ISO 46** 

20 Litre

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 40°c	ASTM D445	mm²/s	41.4	50.6	46.65
Viscosity, Kinematic 100°c	ASTM D445	mm²/s			6.88
Density	ASTM D792	@ 15°c			0.877

#### **Safety Precautions**

**EXPERTS IN HIGH QUALITY OIL** 

Please see our latest EC Safety Data Sheets for details.

#### **Transport Classification**

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 16/10/2024