

# **TECHNICAL DATA SHEET**

**Pro Power** 

# Red Antifreeze & Summer Coolant

1 Litre, 5 Litre, 20 Litre & 199 Litre

## **Product Description**

Pro Power Ultra Red Antifreeze & Summer Coolant is a longlife winter antifreeze and summer coolant, giving up to 5 years of protection. May be used where Glysantin® G12, G12+, G30, G33 or G34 products were originally recommended. Uses OAT - Organic Acid Inhibitor Technology.

Recommended for use by Pro Power for the following manufacturer's specifications

AFNOR: NF R15-601 ASTM: D3306 & D4985 BS: 6580:2010 CUNA: NC 956-16 SAE: J1034 UNE: 26361-88 FFV HEFT: R443 JIS: K 2234 NATO: S 759



MAINTAINS OEM WARRANTY\*

\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	X565-001	5020618211471
5 Litre	X565-005	5020618211549
20 Litre	X565-020	5020618211488
199 Litre	X565-199	5020618211495

#### **Product Benefits**

\* Protects against corrosion, overheating and freezing\* Includes a bittering agent to help prevent accidental swallowing of the product

#### **Product Usage**

Use as per the component manufacturers recommendations.

#### **Storage Instructions**

Store sealed and upright in a cool dry place & out of the reach of children.

#### Shelf Life

5 Years from date of manufacture.

Revision: 3 | Date: 20/01/2025

For further information visit www.propoweroil.com



Pro Power

# **Red Antifreeze & Summer Coolant**

1 Litre, 5 Litre, 20 Litre & 199 Litre

**Specification Information** 

Freeze Protection:

**EXPERTS IN HIGH QUALITY OIL** 

-12°C freeze protection- dilute @ 33% (1 part Antifreeze to 2 parts water). -22°C freeze protection- dilute @ 50% (1 part Antifreeze to 1 part water).

Appearance	:	Pink/Red liquid		
Odour	:	Odourless		
Solubility	:	Miscible in water		

Test	Method	Unit	Min.	Max.	Typical
Freezing Point		°C		-22	

### **Safety Precautions**

Please see our latest EC Safety Data Sheets for details.

### **Transport Classification**

Please see our latest EC Safety Data Sheets for details.

Revision: 3 | Date: 20/01/2025

For further information visit www.propoweroil.com