

TECHNICAL DATA SHEET

Pro Power OW-30 LL-12 FE 5 Litre

Product Description

Pro Power Ultra 0W-30 LL-12 FE is a specialist performance engine oil for BMW petrol and diesel engines from model year 2014 onwards, including those fitted with petrol particulate filters and also offers fuel saving technology. Not suitable for engines with 2 or 3 turbos.

Recommended for use by Pro Power for the following manufacturer's specifications

ACEA: A5/B5 & C2 API: SP & SP RC BMW: LL-12 FE Ford: WSS-M2C950-A MB: 227.61 & 229.61

XPERTS IN HIGH QUALITY OIL



* Image for illustrative purposes only.

| Size | Part No | Barcode |
|---------|----------|---------------|
| 5 Litre | A360-005 | 5020618211556 |

Revision: 1 | Date: 22/10/2024

Product Benefits

- * Premium motor oil recommended for many modern BMW vehicles from model year 2014 onwards
- * Ideal for BMW petrol and diesel engine vehicles including those with petrol / diesel
- particulate filters
- * Exceptional low temperature characteristics meaning that the oil circulates quickly even in the most demanding cold start conditions

Product Usage

Use as per engine manufacturers recommendations.

Storage Instructions

Store sealed and upright in a cool dry place & out of the reach of children.

Shelf Life

5 Years from date of manufacture.

| Appearance | : | Amber liquid |
|-------------------------|---|--------------------|
| Odour | : | Characteristic |
| Solubility | : | Insoluble in water |
| Percentage of Biodiesel | : | Nil |

MAINTAINS OEM WARRANTY*

For further information visit www.propoweroil.com



TECHNICAL DATA SHEET

Pro Power 0W-30 LL-12 FE

5 Litre

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|------------|----------|------|-------|---------|
| Viscosity, Kinematic 100°c | ASTM D445 | mm²/s | 9.3 | <12.5 | 11 |
| Viscosity, CCS | ASTM D4684 | mPa.s | | 6200 | |
| Total Base Number | ASTM D2896 | mg KOH/g | 7 | | 8 |
| HTHS Viscosity | ASTM D4683 | mPa.s | 2.9 | <3.5 | |
| NOACK Volatility | ASTM D5800 | % | | 11 | |
| Viscosity, Kinematic 40°c | ASTM D445 | mm²/s | | | 58.7 |
| Density | ASTM D792 | @ 15°c | | | 0.85 |
| Viscosity Index | ASTM D2270 | | | | 183 |

Safety Precautions

EXPERTS IN HIGH QUALITY OIL

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Revision: 1 | Date: 22/10/2024

For further information visit www.propoweroil.com