

PRO+POWER ULTRA

Technical Data Sheet Pro Power Ultra UTTO



Product details :

Pro Power Ultra UTTO is designed to protect transmission components, reduce brake chatter, clutch slippage and minimise final drive wear. Pro Power Ultra UTTO can also be used in hydraulic systems

- High performance additives for wet brake and power take-off clutches
- Increased water tolerance reduces the risk of blocking filters
- High levels of corrosion and rust inhibition
- Specially selected additives helps to preserve seals and stops leaks

Recommended for use in vehicles requiring :

- API GL-4
- John Deere J20C, J20A
- Massey Ferguson M1145, M1143, M1141, M1135
- Case MAT 3525, MS 1206, MS 1210
- New Holland NH 420A, NH 410B
- Volvo WB101, 97303
- Ford ESN-M2C134-D, ESN-M2C86-B
- ZF TE-ML 03E, 05F, 06K, 17E, 21F
- Kubota UDT
- Allison C-4
- Caterpillar TO-2
- Valtra G2-08

Part numbers :

F102-020	20ltr
F102-199	199ltr
F102-IBC	IBC - 1,000ltr
F102-BLK	Bulk from 500ltr

Typical test data :

Appearance	Clear and bright
Colour	Amber
Specific gravity @ 15.6°C	0.883
Kinematic viscosity @ 100°C (cSt)	9.70
Kinematic viscosity @ 40°C (cSt)	61.9
Viscosity index	141
Flash point COC (°C)	224
Pour point (°C)	-38

For further information visit www.propoweroil.com