

PRO+POWER ULTRA

Technical Data Sheet

Red Antifreeze & Summer Coolant



Product details :

Red Antifreeze & Summer Coolant, is a longlife winter antifreeze and summer coolant, giving up to 5 years of protection

- May be used where Glysantin® G12, G12+, G30, G33 or G34 products were originally recommended
- Uses OAT - Organic Acid Inhibitor Technology
- Protects against corrosion, overheating and freezing
- Includes a bittering agent to help prevent accidental swallowing of the product

Recommended for use in vehicles requiring :

ASTM D3306, ASTM D 4985, SAE J 1034, BS 6580 (2010), AFNOR NF R15-601*, FFV Heft R443 CUNA NC 956-16, UNE 26361-88, JIS K 2234*, NATO S 759

(* with the exception of reserve alkalinity)

It also meets the requirements of the following OEM specifications:

Chrysler MS 9176, Cummins 85T8-2 & 90T8-4, Ford ESE M97B49-A, WSS-M97B44-D & ESD M97 B49-A

GM 1899 M, US 6277 M & OPEL GM QL130100, John Deere H 24 B1 & C1

Leyland Trucks LTS 22 AF 10, Mack 014GS 17004, MAN 248, 324 (SNF) & B&W D 36 5600

Mercedes MB 325.3, Renault 41-01-001, VAG TL 774F, Volvo

Part numbers :

X565-001	1ltr
X565-005	5ltr
X565-020	20ltr
X565-199	199ltr
X565-IBC	IBC - 1,000ltr

Freeze protection :

Antifreeze	Water	Protection
80%	20%	-38°C
50%	50%	-20°C

For further information visit www.propoweroil.com